

STRIP & SLIT COIL

ALLOYS

Stainless Steel Strip

- Austenitic: 201, 301, 301 HY, 301Si, 302, 304, 304L, 305, 316, 316L, 316Ti, 317, 321, 347
- PH/Precipitation Hardening: 15-7, 17-4, 17-7
- Ferritic: 409, 430, 434, 439, 444
- Martensitic: 410, 320
- Contact us for additional alloys.

Carbon Steel Strip

- 1008, 1010, 1050, 1060, 1070, 1074, 1075, 1095

Specialty Metals Strip

- Nickel Alloys: Monel® 400, Inconel® 600/625/X750, Hastelloy®X, Hastelloy®C276, Incoloy® 800H/825, Alloy 20, A286, Ni201, AL-6XN®
- Duplex Grades: 2205, 2305, 2507
- Titanium Grades: 1, 2, 4

Red Metals Strip

- Phosphor Bronze, Beryllium Copper

DIMENSIONAL CAPABILITIES

Thickness

- Min 0.0019" (0.0483 mm) to max 0.062" (1.565 mm)

Width

- Width: 0 .024" (0.6096 mm) to max 24" (609.6 mm)

Precision Slitting

- We provide precision slitting to extremely close tolerances.

Contact us for sizes & tempers outside of listed ranges.

TOLL SERVICES

- Precision Slitting, Edging, & Oscillate Winding Services
- Stainless, Carbon, Specialty Metals, Aluminum, Red Metals, & More

EDGES / SKIVING OPTIONS

- #1 Round Edge
- #3 Slit Edge
- #5 Deburred Edge
- Custom Edges

TEMPERS

- Annealed
- 1/8 hard
- 1/4 hard
- 1/2 hard
- 3/4 hard
- Full Hard
- High Yield (XFH)
- High-Silicon

Custom tempers available for precision rolled coil.

PACKAGING

- Pancake/Ribbon Wound Coils
- Coils on Cores
- Traverse/Oscillate Wound on Spools & Reels from 20 lbs. to 2000 lbs.

The items listed are a portion of the products and alloys we supply.



Gibbs Interwire

Locations in the USA, Canada, & Mexico

Phone: 800-800-4422 • Intl: +1.860.621.0121

• Inquiry@gibbswire.com

• www.gibbswire.com • ISO 9001:2015

STRIP & SLIT COIL

ALLOYS

Stainless Steel Strip

- ▶ Austenitic: 201, 301, 301 HY, 301Si, 302, 304, 304L, 305, 316, 316L, 316Ti, 317, 321, 347
- ▶ PH/Precipitation Hardening: 15-7, 17-4, 17-7
- ▶ Ferritic: 409, 430, 434, 439, 444
- ▶ Martensitic: 410, 320
- ▶ Contact us for additional alloys.

Carbon Steel Strip

- ▶ 1008, 1010, 1050, 1060, 1070, 1074, 1075, 1095

Specialty Metals Strip

- ▶ Nickel Alloys: Monel® 400, Inconel® 600/625/X750, Hastelloy®X, Hastelloy®C276, Incoloy® 800H/825, Alloy 20, A286, Ni201, AL-6XN®
- ▶ Duplex Grades: 2205, 2305, 2507
- ▶ Titanium Grades: 1, 2, 4

Red Metals Strip

- ▶ Phosphor Bronze, Beryllium Copper



DIMENSIONAL CAPABILITIES

Thickness

- ▶ Min 0.0019" (0.0483 mm) to max 0.062" (1.565 mm)

Width

- ▶ Width: 0 .024" (0.6096 mm) to max 24" (609.6 mm)

Precision Slitting

- ▶ We provide precision slitting to extremely close tolerances.

Contact us for sizes & tempers outside of listed ranges.

TOLL SERVICES

- ▶ Precision Slitting, Edging, & Oscillate Winding Services
- ▶ Stainless, Carbon, Specialty Metals, Aluminum, Red Metals, & More

EDGES / SKIVING OPTIONS

- ▶ #1 Round Edge
- ▶ #3 Slit Edge
- ▶ #5 Deburred Edge
- ▶ Custom Edges

TEMPERS

- ▶ Annealed
- ▶ 1/8 hard
- ▶ 1/4 hard
- ▶ 1/2 hard
- ▶ 3/4 hard
- ▶ Full Hard
- ▶ High Yield (XFH)
- ▶ High-Silicon

Custom tempers available for precision rolled coil.

PACKAGING

- ▶ Pancake/Ribbon Wound Coils
- ▶ Coils on Cores
- ▶ Traverse/Oscillate Wound on Spools & Reels from 20 lbs. to 2000 lbs.

The items listed are a portion of the products and alloys we supply.

Gibbs Interwire

Locations in the USA, Canada, & Mexico

Phone: 800-800-4422 ▶ Intl: +1.860.621.0121

▶ Inquiry@gibbswire.com

▶ www.gibbswire.com ▶ ISO 9001:2015

Strip & Slit Coil

ALLOYS

Stainless Steel Strip

- Austenitic: 201, 301, 301 HY, 301Si, 302, 304, 304L, 305, 316, 316L, 316Ti, 317, 321, 347
- PH/Precipitation Hardening: 15-7, 17-4, 17-7
- Ferritic: 409, 430, 434, 439, 444
- Martensitic: 410, 320
- Contact us for additional alloys.

Carbon Steel Strip

- 1008, 1010, 1050, 1060, 1070, 1074, 1075, 1095

Specialty Metals Strip

- Nickel Alloys: Monel® 400, Inconel® 600/625/X750, Hastelloy®X, Hastelloy®C276, Incoloy® 800H/825, Alloy 20, A286, Ni201, AL-6XN®
- Duplex Grades: 2205, 2305, 2507
- Titanium Grades: 1, 2, 4

Red Metals Strip

- Phosphor Bronze, Beryllium Copper

DIMENSIONAL CAPABILITIES

Thickness

- Min 0.0019" (0.0483 mm) to max 0.062" (1.565 mm)

Width

- Width: 0 .024" (0.6096 mm) to max 24" (609.6 mm)

Precision Slitting

- We provide precision slitting to extremely close tolerances.

Contact us for sizes & tempers outside of listed ranges.

TOLL SERVICES

- Precision Slitting, Edging, & Oscillate Winding Services
- Stainless, Carbon, Specialty Metals, Aluminum, Red Metals, & More

EDGES / SKIVING OPTIONS

- #1 Round Edge
- #3 Slit Edge
- #5 Deburred Edge
- Custom Edges

TEMPERS

- Annealed
- 1/8 hard
- 1/4 hard
- 1/2 hard
- 3/4 hard
- Full Hard
- High Yield (XFH)
- High-Silicon

Custom tempers available for precision rolled coil.

PACKAGING

- Pancake/Ribbon Wound Coils
- Coils on Cores
- Traverse/Oscillate Wound on Spools & Reels from 20 lbs. to 2000 lbs.

The items listed are a portion of the products and alloys we supply.



Gibbs Interwire

Locations in the USA, Canada, & Mexico

Phone: 800-800-4422 • Intl: +1.860.621.0121

• Inquiry@gibbswire.com

• www.gibbswire.com • ISO 9001:2015